



- Light sources: White LED
- Ballast: The power source is included in the scope of supply
- Body material: Aluminium alloy
- Dome lamp material: Transparent or opal PET
- Diffuser: Additional option
- Coating: Polyether powder coating in any colour from the standard colour range
- Connection: The max. section of the connected conductors is up to 4 mm². Electric shock protection class - 1

Modern Martini LED

ERC
220V
IP54
LED
3000K
4000K

| | Code | Power, W | Dome | Light flux, lm | Weight, kg |
|---|------------------|----------|------|----------------|------------|
| 1 | ML-LO 3K(4K) | 40 | O | 3215 | 7,5 |
| | ML-HI 3K(4K) | 84 | O | 5812 | 7,5 |
| | ML-LO-WSM 3K(4K) | 40 | T | 3911 | 7,5 |
| 2 | ML-HI-WSM 3K(4K) | 84 | T | 7072 | 7,5 |
| | ML-LO-WAS 3K(4K) | 40 | T | 3911 | 7,5 |
| | ML-HI-WAS 3K(4K) | 84 | T | 7072 | 7,5 |
| 3 | ML-LO-ES 3K(4K) | 40 | T | 3911 | 7,5 |
| | ML-HI-ES 3K(4K) | 84 | T | 7027 | 7,5 |

| | Code | Power, W | Dome | Light flux, lm | Weight, kg |
|--|-----------------|----------|------|----------------|------------|
| | ML-LO-ES 3K(4K) | 40 | T | 3911 | 7,5 |
| | ML-HI-ES 3K(4K) | 84 | T | 7027 | 7,5 |

- T / O - dome material, opal (O) or transparent (T)
- LO / HI - power, high (HI) or low (LO)
- WSM - wide symmetrical optics, WAS - wide asymmetrical optics
- ES - transparent antidazzle diffuser (eyes safety) "Crushed Ice"

A luminaire order code consists of the product code - the body colour code from the standard colour range, for instance: ML - LO 4K - GR/MM

