



Light sources: ILB/CFL of up to 52 W with base E27 or LED.

Power supply: The power source is included in the scope of supply.

Design: Body - plastic, coating - powder coating. Installation - on the wall or on the ceiling. Protection class - IP65.

Diffuser: Dome - opal impact-resistant polycarbonate.

Coating: Body colour:
White (additional code - W);
Black (additional code - B);
Grey metallic RAL 9006 Silver (additional code - M).

Connection: To a 220 V, 50 Hz network, via a terminal block installed in the body of the luminaire.

The max. section of the connected conductors is up to 4 mm².

Facade Drop



Code	Power, W	Light source	Lamp holder	Light flux, lm	Weight, kg
DROP 1	max. 1x22	ILB/CFL	1 x E27	-	1,27
DROP 1x2	max. 2x13	ILB/CFL	2 x E27	-	1,27
DROP 2	max. 1x38	ILB/CFL	1 x E27	-	1,53
DROP 2x2	max. 2x26	ILB/CFL	2 x E27	-	1,53
DROP 1 3K	14	LED 3000K	-	1500	1,0
DROP 1 4K	14	LED 4000K	-	1500	1,0
DROP 2 3K	22	LED 3000K	-	2400	1,24
DROP 2 4K	22	LED 4000K	-	2400	1,24
Code	Power, W	Light source	Lamp holder	Light flux, lm	Weight, kg

A luminaire order code consists of the product code - the product colour code from the standard colour range, for instance: DROP 2 - W