


Light sources: LED strip IP65.
 Colour grade: white - 3000K(4000K), CRI 70
 Power voltage 24V, DC.

Power supply / Ballast: Ordered separately.
 The recommended power supplies:
 ARPV-LG24100 (24V, 4A, 100W, PFC) Arlight
 ARPV-LG24150 (24V, 6A, 150W, PFC) Arlight
 CLG-100-24 Mean Well (24V, 100W, PFC)
 HLG-120H-24 Mean Well (24V, 100W, PFC)
 HLG-150H-24 Mean Well (24V, 100W, PFC)

Design: Polycarbonate with UV protection.
 Protection class - IP65.
 Mounting: on a horizontal or vertical surface using special brackets being a part of the luminaire structure. Body length - up to 2,5 meters.

Connection: The max. section of the connected conductors is up to 4 mm². Electric shock protection class - 2.

Facade Microline



Code	Power, W	Color temperature	Light flux, lm	Quantity of brackets	Length, mm	Weight, kg
Microline 300 3K(4K)	3	3000K/4000K	190	2	320	0,17
MicroLine 300 A/R/G/B	3	-	-	2	320	0,17
Microline 500 3K(4K)	5	3000K/4000K	315	2	520	0,24
Microline 500 A/R/G/B	5	-	-	2	520	0,24
Microline 600 3K(4K)	6	3000K/4000K	380	2	620	0,27
Microline 600 A/R/G/B	6	-	-	2	620	0,27
Microline 800 3K(4K)	8	3000K/4000K	500	2	820	0,35
Microline 800 A/R/G/B	8	-	-	2	820	0,35
Microline 1000 3K(4K)	10	3000K/4000K	630	2	1020	0,42
Microline 1000 A/R/G/B	10	-	-	2	1020	0,42
Microline 1200 3K(4K)	12	3000K/4000K	750	3	1220	0,51
Microline 1200 A/R/G/B	12	-	-	3	1220	0,51
Microline 1500 3K(4K)	15	3000K/4000K	945	3	1520	0,62
Microline 1500 A/R/G/B	15	-	-	3	1520	0,62
Microline 2500 3K(4K)	25	3000K/4000K	1575	4	2520	1,0
Microline 2500 A/R/G/B	24	-	-	4	2520	1,0

Code Power, W Color temperature Light flux, lm Quantity of brackets Length, mm Weight, kg

A luminaire order code : Microline 2500 - 3K (the light code)