



Components
Included with the product are light sources (a metalhalide lamp, fluorescent lamps and LED).

Design
2 modifications:
1. Steel.
2. Stainless steel.
The dome lamp material – opal polycarbonate.

Connection
220 V, 50 Hz

Additional information
Base for installation - FM1T, 3T-1000 or embedded anchors ANK-R (p.206-211).
Corrosion protection - HD galvanizing (for option 1).

Cooling
Powder coating in any colour from the standard colour range (p. 213).

Ignis Replay

EAC
220V
IP54
LED
RGB
3000K
4000K

Code	H, m	Power, W / Light source	Light flux, lm	Weight, kg
option 1				
TRE15	1,5	150 / ДРИ	-	32
TRE20	2,0	150 / ДРИ	-	34
TRE30	3,0	150 / ДРИ	-	36
option 2				
TRE-N25	2,5	3 x 35 / T5	-	12
TRE-N25 LED 3K(4K)	2,5	80 / LED	4095	12
TRE-N25 LED RGB	2,5	80 / LED RGB	-	12
TRE-N30 LED 3K(4K)	3,0	100 / LED	5460	14
TRE-N30 LED RGB	3,0	100 / LED RGB	-	14
Code	H, m	Power, W	Light flux, lm	Weight, kg

A bollard order code consists of the product code - the product colour code from the standard colour range, for instance:: TRE-N25 LED 3K - BLK/MT